

| Art.No.   | article name                                                                      |
|-----------|-----------------------------------------------------------------------------------|
| 108102006 | STANDARD - earthed socket outlet with central earth contact, colour: arctic white |

STANDARD - surface mount earthed socket outlet with central earth contact, 1-fold, without shutter, 16A, 250V~, IP20, colour: arctic white



| Technical data                          |                     | 108102006 |
|-----------------------------------------|---------------------|-----------|
| Connection type                         | Push-in clamp       |           |
| With signal lamp                        | no                  |           |
| With enhanced contact protection        | no                  |           |
| Frequency                               | 50 - 50             |           |
| Label space/information surface         | no                  |           |
| Eject-mechanism                         | no                  |           |
| Material                                | Plastic             |           |
| Rated fault current                     | 0.00 A              |           |
| Type of fastening                       | Mounting with screw |           |
| Impact strength                         | IK00                |           |
| Transparent                             | no                  |           |
| With miniature fuse                     | no                  |           |
| With loop through function              | yes                 |           |
| With function lighting                  | no                  |           |
| With orientation lighting               | no                  |           |
| Number of modules (module system)       | 0                   |           |
| Number of active pins (round)           | 1                   |           |
| Number of active pins (flat)            | 0                   |           |
| Min. depth of built-in installation box | 0.0 mm              |           |
| Compatible with Apple HomeKit           | no                  |           |
| Compatible with Google Assistant        | no                  |           |
| Compatible with Amazon Alexa            | no                  |           |
| Metallic colour                         | no                  |           |
| Nominal current                         | 16.00 A             |           |
| Nominal voltage                         | 250 V               |           |
| Mounting method                         | Aufputz             |           |
| Colour                                  | White               |           |
| Model                                   | Grounding pin       |           |
| Halogen free                            | yes                 |           |
| Lockable                                | no                  |           |
| With hinged lid                         | no                  |           |
| Surface protection                      | Untreated           |           |
| Number of phases                        | 1                   |           |
| With on/off switch                      | no                  |           |
| For heavy conditions (according to VDE) | no                  |           |

| Technical data                           |                         | 108102006 |
|------------------------------------------|-------------------------|-----------|
| Rotated central insert                   | no                      |           |
| Over voltage protection                  | no                      |           |
| Fault current protection                 | no                      |           |
| Insulated mounting                       | no                      |           |
| RAL-number (similar)                     | 9016                    |           |
| Width of device                          | 64.0 mm                 |           |
| Height of device                         | 100.5 mm                |           |
| Depth of device                          | 43.0 mm                 |           |
| Number of socket outlets switchable      | 0                       |           |
| IFTTT support available                  | no                      |           |
| Concurrently switching neutral conductor | no                      |           |
| Special power supply                     | No special power supply |           |
| Material quality                         | Thermoplastic           |           |
| Surface finishing                        | Glossy                  |           |
| Imprint/indication                       | None                    |           |
| Suitable for degree of protection        | IP20                    |           |
| Anti-bacterial treatment                 | no                      |           |
| With built-in bluetooth speaker          | nein                    |           |
| Number of ports USB-A                    | 0                       |           |
| Number of ports USB-C                    | 0                       |           |
| Max. current rating of USB power supply  | 0.00 A                  |           |
| With Wi-Fi signal repeater               | nein                    |           |
| Colour of switch operator                | not applicable          |           |
| Protective contact                       | flat                    |           |
| Concurrently switching neutral conductor | 0                       |           |
| Number of loop throughs                  | 1                       |           |
| Farbe (Kopp-Bezeichnung)                 | arctic white            |           |