

Art.No.	article name
120101001	2-way multiple socket outlet, reconnectable, without cable

2-way multiple socket outlet, reconnect able, without cable



Abb. ähnlich  
Fig. similar

Technical data	120101001
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	2
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	White
core cross section	0.0 mm <sup>2</sup>
Halogen free	yes
Surface protection	Untreated
Length of power cord	0 m
With on/off switch	no
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9016
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no
Number of socket outlets Swiss standard type 13	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data	120101001
Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0
Number of socket outlets Italian standard type P17	0
Degree of protection (IP)	IP20
Material quality	Duroplast
NEMA designation	None
Surface finishing	Matt
Angle rotated central insert	90°
Type of mains connection	Other
Number of socket outlets Danish standard (earthing pin)	0
Number of socket outlets British Standard BS1363	0
Anti-bacterial treatment	no
Number of socket outlets Italian standard type P30	0
Overcurrent protection	nein
Max. connected load	3680 W
Number of socket outlets CEE 7/1 (no protective contact)	0
Farbe (Kopp-Bezeichnung)	arctic white