

Art.No. article name

120915855 6-way multiple socket outlet, with illuminated switch (2-pole), colour: black

Set of 2 pieces multiple socket outlet 6-way, with illuminated switch (2-pole), with 45° turned sockets, with shutter, cable H05VV-F3G1,5mm², 1,4m, 16A, 250V~, colour: black



Technical data 120915855

Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	6
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of CEE socket outlets	0
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Black
core cross section	1.5 mm ²
Halogen free	no
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	yes
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9011
Number of socket outlets CEE 7/16 (EURO)	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 28.02.2024

Technical data		120915855
IFTT support available	no	
Number of socket outlets Swiss standard type 13	0	
Number of socket outlets Swiss standard type 15	0	
Number of socket outlets Swiss standard type 23	0	
Number of socket outlets Swiss standard type 25	0	
Number of socket outlets Italian standard type P17	0	
Degree of protection (IP)	IP20	
Material quality	Duroplast	
NEMA designation	None	
Surface finishing	Matt	
Angle rotated central insert	45°	
Type of mains connection	Protective contact (SCHUKO)	
Number of socket outlets Danish standard (earthing pin)	0	
Number of socket outlets British Standard BS1363	0	
Anti-bacterial treatment	no	
Number of socket outlets Italian standard type P30	0	
Overcurrent protection	nein	
Max. connected load	3680 W	
Directly pluggable (without power cord)	nein	
Number of socket outlets CEE 7/1 (no protective contact)	0	