

Art.No.	article name
---------	--------------

128615854	3-way multiple socket outlet, colour: black
-----------	---

Set of 2 pieces multiple socket outlet 3-way, with 45° turned sockets, with shutter, cable H05VV-F3G1,5mm², 1,4m, 16A, 250V~, colour: black



Technical data	128615854
----------------	-----------

Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	3
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of CEE socket outlets	0
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Black
core cross section	1.5 mm ²
Halogen free	no
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	no
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9011
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 29.02.2024

Technical data		128615854
Number of socket outlets Swiss standard type 13	0	
Number of socket outlets Swiss standard type 15	0	
Number of socket outlets Swiss standard type 23	0	
Number of socket outlets Swiss standard type 25	0	
Number of socket outlets Italian standard type P17	0	
Degree of protection (IP)	IP20	
Material quality	Duroplast	
NEMA designation	None	
Surface finishing	Matt	
Angle rotated central insert	45°	
Type of mains connection	Protective contact (SCHUKO)	
Number of socket outlets Danish standard (earthing pin)	0	
Number of socket outlets British Standard BS1363	0	
Anti-bacterial treatment	no	
Number of socket outlets Italian standard type P30	0	
Overcurrent protection	nein	
Max. connected load	3680 W	
Directly pluggable (without power cord)	nein	
Number of socket outlets CEE 7/1 (no protective contact)	0	