

Art.No.	article name
142116016	PRCD-S, mobile protective device, 3-pole, 0,03A, with extension and carrying case, plug and 3-way coupling (solid rubber)

PRCD-S, with protective conductor monitoring, 3-pole switching, residual current 0,03A, type A, 230V, 16A, 50Hz, IP44, in solid case, plug (solid rubber) and 3-fold coupling (solid rubber) with covers, cable lengths: 150cm plug, 300cm coupling, Cable: H07RN-F3G1,5mm<sup>2</sup>



Technical data	142116016
Voltage type	AC Hz
Rated insulation voltage Ui	1500 V
Number of poles	3
Rated fault current	0.03 A
Surge current capacity	0.025 kA
Pollution degree	2
Connectable conductor cross section multi-wired	1,50 2,50 mm <sup>2</sup>
With interlocking device	no
Additional equipment possible	no
Mounting method	Cable
Rated current	16.00 A
Rated voltage	230 V
Explosion-proof	no
Ambient temperature during operating	-25 40 °C
Rated impulse withstand voltage Uimp	2.50 kV
Degree of protection (IP)	IP44
Leakage current type	A
Frequency	50 Hz
Short-time delayed tripping	no
Short-circuit breaking capacity (Icw)	1.500 kA
Selective protection	no
Packaging break	J