

Art.No.	article name
143205043	Extension lead, grounding-Type plug and earthed coupling with 3m cable, with shutter

Extension lead, IP20, 16A, 250V~, protective contact angle pug and earthed coupling with cable H05VV-F 3Gx1,5mm<sup>2</sup>, 3m, with shutter, black



Technical data	143205043
Nominal cross section conductor	1.50 mm <sup>2</sup>
Frequency	50 50 Hz
Length mm	3000.0 mm
Spiralized cable	no
Nominal voltage	230,00 230,00 V
Connector system system-oriented	no
Nominal current	16.00 A
Number of cores	3
Oil resistant according to EN IEC 60811-404	no
With protective conductor	yes
Degree of protection (IP)	IP20
With cord switch	no
Colour outer sheath	Black
Material outer sheath	Polyvinyl chloride (PVC)
Reaction-to-fire according to EN 13501-6: Class	None
Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None
Reaction-to-fire according to EN 13501-6: Acidity	None
Connection 1	Protective contact plug CEE 7/4 (type F)
Connection 2	Coupler with protective contact (SCHUKO)
Cable entry connection 1	abgewinkelt
Cable entry connection 2	gerade
Packaging break	N