

Art.No.	article name
145210047	Rubber extension lead, earthed, solid rubber plug and 3-way coupling, with 10m rubber cable, colour: black

Rubber extension lead, 16A, 250V~, earthed, solid rubber plug and 3-way earthed coupling with rubber cable H07RN-F 3x1,5mm², 10m, protection class IP44, colour: black



Technical data	145210047
Nominal cross section conductor	1.50 mm ²
Frequency	50 50 Hz
Length mm	10000.0 mm
Spiralized cable	no
Nominal voltage	230,00 230,00 V
Connector system system-oriented	no
Nominal current	16.00 A
Number of cores	3
Oil resistant according to EN IEC 60811-404	no
With protective conductor	yes
Degree of protection (IP)	IP20
With cord switch	no
Colour outer sheath	Black
Material outer sheath	Rubber
Reaction-to-fire according to EN 13501-6: Class	None
Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None
Reaction-to-fire according to EN 13501-6: Acidity	None
Connection 1	Protective contact plug CEE 7/4 (type F)
Connection 2	Coupler with protective contact (SCHUKO)
Cable entry connection 1	gerade
Connection type according to IEC 60320, connection 1	sonstige
Cable entry connection 2	gerade
Connection type according to IEC 60320, connection 2	sonstige
Packaging break	N