

Art.No.	article name
148606010	PRCD-S pro, portable protective device, 3-pole, 0.03A, with extension and carrying case, plug (IP68) and coupling (IP68) for fire departments

PRCD-S pro, with protective conductor monitoring, 3-pole switching, rated residual current 0.03A, type A, 230V, 16A, 50Hz, IP55, in solid case, plug IP68, coupling 1-fold IP68, cable lengths: plug - PRCD-S pro=150cm, plug - coupling=300cm, cable: H07RN-F3G2,5mm², for fire departments



Technical data	148606010
Voltage type	AC Hz
Rated insulation voltage Ui	1500 V
Number of poles	3
Rated fault current	0.03 A
Surge current capacity	0.025 kA
Pollution degree	2
Connectable conductor cross section multi-wired	1,50 2,50 mm ²
With interlocking device	no
Additional equipment possible	no
Mounting method	Cable
Rated current	16.00 A
Rated voltage	230 V
Explosion-proof	no
Ambient temperature during operating	-25 45 °C
Rated impulse withstand voltage Uimp	2.50 kV
Degree of protection (IP)	IP55
Leakage current type	A
Frequency	50 Hz
Short-time delayed tripping	no
Short-circuit breaking capacity (Icw)	1.500 kA
Selective protection	no
Packaging break	N