

Art.No.	article name
151302017	Textile cable, twisted, 2m, H05V-K 2x0,75mm, beige

Twisted textile cable, 2-core, 2m, closed with cable ties, with braided nylon textile jacket, H05V-K 2x0,75mm<sup>2</sup>, color: beige



Technical data	151302017
Nominal cross section conductor	0.75 mm <sup>2</sup>
Halogen free (according to IEC 60754-2)	no
Low smoke according to EN IEC 61034-2	no
Max. conductor temperature	80 °C
Core identification according to HD 308 S2	yes
Weight	60.000 kg
Nominal voltage U	250 V
Torsion resistant	yes
Number of pilot/reduced cores	0
Number of cores	2
Oil resistant according to EN IEC 60811-404	yes
Low temperature resistant (according to EN 60811-504+505+506)	yes
Conductor resistance at 20 °C	26 Ohm/km
Colour outer sheath	Other
Shape of conductor	Round
Conductor material	Copper
Screen over stranding element	None
Screen over stranding	None
Material outer sheath	Polyvinyl chloride (PVC)
Conductor category	Class 1 = solid
Armouring/reinforcement	Wire
Suspension element	Aramid fibre
Conductor surface	Other
Reaction-to-fire according to EN 13501-6: Class	None
Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None
Reaction-to-fire according to EN 13501-6: Acidity	None
AWG size	18
Specification core insulation	Other
Specification material outer sheath	Other
Material reinforcement	Copper
Cable geometry	Round
Protective barrier	Polyvinyl chloride (PVC)

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 10.04.2024

Technical data		151302017
Material core insulation	Polyvinyl chloride (PVC)	
Core identification	Colour	
Flame retardant according to IEC 60332-1-2	yes	
Farbe (Kopp-Bezeichnung)	beige	