

Art.No. article name

194441018 LED round lamp, 10W, colour: grey

LED round lamp, 10W, with 28 SMD2835 LEDs, luminous flux: 700lm, colour temperature: 6500K, 220-240V~, 50Hz, beam angle: 120°, lifetime: 30000 hours, material: PP housing and PC diffuser, LED module is not exchangeable, colour: grey



Technical data 194441018

Connection type	Screwed terminal
Colour housing	Anthracite
Lamp holder	Other
Voltage type	AC Hz
With movement sensor	no
Length mm	0.0 mm
Height/depth	8.0 mm
Suitable for light line configuration	no
Suitable for emergency lighting	no
Impact strength	IK00
Nominal voltage	220,00 240,00 V
Emergency power supply integrated	no
Suitable for workplace according to EN 12464-1	no
Suitable for surface mounting	no
Constant light output (CLO)	no
Dimming 0-10 V	no
Dimming 1-10 V	no
Dimming DALI	no
Dimming DMX	no
Dimming potentiometer (integrated)	no
Dimming LineSwitch	no
Dimming manufacturer's proprietary system	no
Dimming mains voltage modulation	no
Dimming phase cut-off	no
Dimming phase cut-on	no
Dimming programmable	no
Dimming RF	no
Dimming Sine Wave Reduction	no
Dimming Touch and Dim	no
Dimming Zigbee	no
Dimming with push-button	no
No dim function	no
Dimming DSI	no
Operation by Bluetooth	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 10.04.2024

Technical data	194441018
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Dimming DALI-2	no
Flickering value Pst LM	0.012 N
Width	21.5 mm
Outer diameter	21.5 mm
Suitable for wall mounting	yes
With light sensor	no
Suitable for suspended mounting	no
Luminous intensity	384
Luminaire with limited surface temperature, sign "D"	no
Covering of the luminaire with thermally insulating material possible	no
Suitable for built-in mounting	no
Max. system power	10.0 W
Rated luminous flux according to IEC 62722-2-1	700 lm
With air slots	no
IFTTT support available	no
Degree of protection (IP)	IP54
With light source	yes
Type of grid	Other
Colour rendering index CRI	80-89
Material housing	Plastic
Lamp type	LED not exchangeable
Colour of light	Other
Type of wiring	Suitable for through wiring
Filament test according to IEC 60695-2-11	None
Light distributor	Other
Light outlet	Direct
Light sharing	Symmetric
Material cover	Plastic, opal
Beam angle	Extreme wide beam >80°
Protection class	II
Colour temperature	6500 6500 K
Compatible with Casambi	nein
Beam angle adjustable	nein
Luminous flux adjustable	nein
Colour of light adjustable	nein
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Suitable for ceiling mounting	ja
Surface protection housing	unbehandelt
Exchangeable control gear	nein

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 10.04.2024