Art.No.	article name
196300018	PRCD-S, mobile protective device, 3-pole, 0,01A, IP55

PRCD-S, with protective conductor monitoring, 3-pole switching, residual current 0,01A, type A, 230V, 16A, 50Hz, IP55

Technical data	*196300018*
Voltage type	AC
Rated insulation voltage Ui	1500 V
Number of poles	3
Rated fault current	0.01 A
Surge current capacity	0.250 kA
Pollution degree	2
Connectable conductor cross section multi-wired	1.50 - 2.50 mm²
With interlocking device	no
Additional equipment possible	no
Mounting method	Cable
Built-in depth	0.0 mm
Rated current	16.00 A
Rated voltage	230 V
Explosion-proof	no
Ambient temperature during operating	-25 - 40 °C
Rated impulse withstand voltage Uimp	2.50 kV
Degree of protection (IP)	IP55
Leakage current type	A
Frequency	50 Hz
Short-time delayed tripping	no
Short-circuit breaking capacity (Icw)	1.500 kA
Selective protection	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *10.08.2026*