

Art.No.	article name
196402082	PAN Minimeter NEW, digital multimeter CAT III 600V with contactless voltage tester

PAN Minimeter NEW, digital multimeter CAT III 600V with contactless voltage tester, three-step display, 1-pole phase test with acoustic alarm, illuminated digital display 1999, LED torch, battery test, diode test, data hold, automatic switch-off, dimensions 70x150x50mm, CAT III 600V, scope of delivery: test cable, AAA battery 2x1.5V, operating instructions



Technical data	196402082
Measured value memory	no
True RMS measurement	no
Continuity test	yes
Interface	no
Capacitance measurement	no
Frequency measurement	no
With decibel measurement (dB)	no
Explosion-tested version	no
Analogue bar graph display	no
Bluetooth interface	no
Min. value storage	no
Nominal test voltage 100 V	no V
Nominal test voltage 1000 V	no V
Nominal test voltage 250 V	no V
Nominal test voltage 500 V	no V
Relative value measurement	no
Analogue bar graph display analogue/logarithmical	no
Milliohm measurement with 4 wire technique (Kelvin connection)	no
Temperature measurement RTD	no
Temperature measurement TC	no
Nominal test voltage 10 V	no V
Nominal test voltage 50 V	no V
Cable length measurement	no
Cable symmetry testing for two wire connections a-b-E	no
Power and energy measurement	no
Harmonics analysis/power quality	no
Rotational speed measuring	no
Automatic circuit breaker	no
Max. voltage measuring circuit category	600 V
IR interface	no
Resistance test/diode test	yes

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data		196402082
Inductance measurement	no	
With conductivity measurement	no	
Max. voltage measuring range, AC	600 V	
Max. current measuring range, DC	10.00 A	
Max. resistance measuring range	20 MOhm	
Max. value storage	no	
Multiple display	no	
Peak value memory	no	
Duty cycle measurements	no	
Measuring range selection	Manual	
Lowest resolution, DC voltage	0.1 mV	
Lowest resolution, DC current	1 μ A	
Lowest resolution, AC voltage	100 mV	
Lowest resolution, resistance	0.1 Ohm	
Packaging break	N	