

Art.No.	article name
223012002	4-way multiple socket outlet, with 45° turned sockets with hinged lid, with illuminated switch (2-pole), with shutter, cable 1.4m

Multiple socket outlet 4-fold, protection category IP44, with illuminated switch, with 45° turned sockets, with hinged lid and shutter, cable H07RN-F3xG1,5mm<sup>2</sup>, 1,4m, 16A, 250V~, yellow-black



Technical data	223012002
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	4
Residual current circuit breaker (RCCB)	no
With cover lid	yes
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Black
core cross section	1.5 mm <sup>2</sup>
Halogen free	no
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	yes
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9011
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no

Technical data		223012002
Number of socket outlets Swiss standard type 13	0	
Number of socket outlets Swiss standard type 15	0	
Number of socket outlets Swiss standard type 23	0	
Number of socket outlets Swiss standard type 25	0	
Number of socket outlets Italian standard type P17	0	
Degree of protection (IP)	IP44	
Material quality	Duroplast	
NEMA designation	None	
Surface finishing	Matt	
Angle rotated central insert	45°	
Number of socket outlets Danish standard (earthing pin)	0	
Number of socket outlets British Standard BS1363	0	
Anti-bacterial treatment	no	
Number of socket outlets Italian standard type P30	0	
Overcurrent protection	nein	
Max. connected load	3680 W	
Directly pluggable (without power cord)	nein	
Number of socket outlets CEE 7/1 (no protective contact)	0	
Packaging break	N	