


Art.No.	article name
226820011	POWERversal 7-way, with switch, with shutter, cable 1.4m

POWERversal 7-way, 250V~, 16A, max.3600w, IP20, with illuminated switch (2-pole), with shutter, with 90° turned sockets, 65mm distance between sockets, mountable, reconnectable, cable 05VV-F3G1,5mm², 1,4m, length (lx-bxh):(612,6x71x58,3)mm, silver-black



Technical data	226820011
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	7
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Silver
core cross section	1.5 mm ²
Halogen free	yes
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	yes
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	7035
Number of socket outlets CEE 7/16 (EURO)	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data		226820011
IFTTT support available		no
Number of socket outlets Swiss standard type 13		0
Number of socket outlets Swiss standard type 15		0
Number of socket outlets Swiss standard type 23		0
Number of socket outlets Swiss standard type 25		0
Number of socket outlets Italian standard type P17		0
Degree of protection (IP)		IP20
Material quality		Thermoplastic
NEMA designation		None
Surface finishing		Matt
Angle rotated central insert		90°
Type of mains connection		Plug CEE 7/4 (type F)
Number of socket outlets Danish standard (earthing pin)		0
Number of socket outlets British Standard BS1363		0
Anti-bacterial treatment		no
Number of socket outlets Italian standard type P30		0
Overcurrent protection		nein
Max. connected load		3680 W
Directly pluggable (without power cord)		nein
Type of plug		angled
Number of socket outlets CEE 7/1 (no protective contact)		0
Packaging break		N