

| Art.No.   | article name   |
|-----------|--|
| 227320017 | POWERversal 5-way, with hinged lid and illuminated switch (2-pole), with shutter, cable 1.4m |

POWERversal 5-fold, robust Channel multi-socket-outlet with flap lid, 16A, 250V~, max.3600W, IP20, with increased shutter, switch, 2-pole, illuminate, connecting cable H05VV-F3G1,5mm<sup>2</sup>, 1,4m, 19"/ (482,6x71x58,3mm)



| Technical data  | 227320017           |
|---|---------------------|
| Housing shape   | Rectangular         |
| Number of socket outlets with protective contact (SCHUKO) | 5                   |
| Residual current circuit breaker (RCCB)                   | no                  |
| With cover lid  | yes                 |
| Material  | Plastic             |
| Impact strength   | IK00                |
| Transparent   | no                  |
| With miniature fuse                                       | no                  |
| Number of socket outlets with earth pin                   | 0                   |
| Number of other socket outlets                            | 0                   |
| Number of cold device socket outlets                      | 0                   |
| Number of USB connections                                 | 0                   |
| Number of socket outlets type Bipasso (Italy)             | 0                   |
| Number of socket outlets Type P11 (Italy)                 | 0                   |
| Number of NEMA-outlets                                    | 0                   |
| Number of universal multi standard sockets                | 0                   |
| Number of socket outlets French standard (Type E)         | 0                   |
| Compatible with Apple HomeKit                             | no                  |
| Compatible with Google Assistant                          | no                  |
| Compatible with Amazon Alexa                              | no                  |
| Nominal current   | 16.00 A             |
| Colour  | Silver              |
| core cross section  | 1.5 mm <sup>2</sup> |
| Halogen free  | yes                 |
| Surface protection  | Untreated           |
| Length of power cord                                      | 1.4 m               |
| With on/off switch  | yes                 |
| Mains filter  | no                  |
| Rotated central insert                                    | yes                 |
| Over voltage protection                                   | no                  |
| RAL-number (similar)                                      | 7035                |
| Number of socket outlets CEE 7/16 (EURO)                  | 0                   |
| IFTTT support available                                   | no                  |

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

| Technical data   |                       | 227320017 |
|--|-----------------------|-----------|
| Number of socket outlets Swiss standard type 13          | 0                     |           |
| Number of socket outlets Swiss standard type 15          | 0                     |           |
| Number of socket outlets Swiss standard type 23          | 0                     |           |
| Number of socket outlets Swiss standard type 25          | 0                     |           |
| Number of socket outlets Italian standard type P17       | 0                     |           |
| Degree of protection (IP)                                | IP20                  |           |
| Material quality   | Thermoplastic         |           |
| NEMA designation   | None                  |           |
| Surface finishing  | Matt                  |           |
| Angle rotated central insert                             | 90°                   |           |
| Type of mains connection                                 | Plug CEE 7/4 (type F) |           |
| Number of socket outlets Danish standard (earthing pin)  | 0                     |           |
| Number of socket outlets British Standard BS1363         | 0                     |           |
| Anti-bacterial treatment                                 | no                    |           |
| Number of socket outlets Italian standard type P30       | 0                     |           |
| Overcurrent protection                                   | nein                  |           |
| Max. connected load                                      | 3680 W                |           |
| Directly pluggable (without power cord)                  | nein                  |           |
| Type of plug   | angled                |           |
| Number of socket outlets CEE 7/1 (no protective contact) | 0                     |           |
| Packaging break  | J                     |           |