Art.No.	article name
233105008	UNOversal PLUS 3-fold, with overvoltage filter, illumination switch, with shutter, mountable, 90° turned sockets, 1.4m cable

UNOversal Plus, 3-way, with overvoltage filter, optical overvoltage indicator in case of a fault, with illuminated switch (2-pole), with shutter, with 90° turned sockets, 52mm distance between sockets, cableH05VV-F3G1,5mm², 1, 4m, mountable, 16A, 250V~, anthracite

Technical data	*233105008*
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	3
Residual current circuit breaker (RCCB)	no
With cover lid	yes
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	anthracite
core cross section	1.5 mm²
UV resistant	conditionally
Halogen free	yes
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	no
Mains filter	no
Rotated central insert	no
Over voltage protection	yes
RAL-number (similar)	7016

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *10.02.2026*

Technical data	*233105008*
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no
Number of socket outlets Swiss standard type 13	0
Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0
Number of socket outlets Italian standard type P17	0
Degree of protection (IP)	IP20
Material quality	Duroplast
NEMA designation	None
Surface finishing	Matt
Angle rotated central insert	90°
Type of mains connection	Plug CEE 7/4 (type F)
Number of socket outlets Danish standard (earthing pin)	0
Number of socket outlets British Standard BS1363	0
Anti-bacterial treatment	no
Number of socket outlets Italian standard type P30	0
Overcurrent protection	nein
Max. connected load	3680 W
Directly pluggable (without power cord)	nein
Type of plug	angled
Number of socket outlets CEE 7/1 (no protective contact)	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *10.02.2026*