

Art.No.	article name
233205001	UNOversal PLUS 6-fold, with overvoltage filter, illumination switch, with shutter, mountable, 90° turned sockets, 1.4m cable

UNOversal Plus, 6-way, with overvoltage filter, optical overvoltage indicator in case of a fault, with illuminated switch (2-pole), with shutter, with 90° turned sockets, 52mm distance between sockets, cableH05VV-F3G1,5mm², 1,4m, mountable, 16A, 250V~, anthracite



Technical data	233205001
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	6
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	anthracite
core cross section	1.5 mm ²
Halogen free	yes
Surface protection	Untreated
Length of power cord	1.4 m
Mains filter	no
Rotated central insert	yes
Over voltage protection	yes
RAL-number (similar)	7016
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no

Technical data		233205001
Number of socket outlets Swiss standard type 13	0	
Number of socket outlets Swiss standard type 15	0	
Number of socket outlets Swiss standard type 23	0	
Number of socket outlets Swiss standard type 25	0	
Number of socket outlets Italian standard type P17	0	
Degree of protection (IP)	IP20	
Material quality	Duroplast	
NEMA designation	None	
Surface finishing	Matt	
Angle rotated central insert	90°	
Type of mains connection	Plug CEE 7/4 (type F)	
Number of socket outlets Danish standard (earthing pin)	0	
Number of socket outlets British Standard BS1363	0	
Anti-bacterial treatment	no	
Number of socket outlets Italian standard type P30	0	
Overcurrent protection	nein	
Max. connected load	3680 W	
Directly pluggable (without power cord)	nein	
Type of plug	angled	
Number of socket outlets CEE 7/1 (no protective contact)	0	
Packaging break	N	