

Art.No.	article name
233805009	DUOversal PLUS 3=6, with illuminated switch (2-pole), with shutter, with 35° turned sockets, cable 1.4m, mountable

DUOversal Plus, 3=6, all sockets with connection option for one grounding-type plug or two euro-plugs, with illuminated switch (2-pole), with shutter, with 35° turned sockets, 52mm distance between sockets, cable H05VV-F3G1, 5mm², 1,4m, mountable, 16A, 250V~, anthracite



Technical data		233805009
Housing shape	Rectangular	
Number of socket outlets with protective contact (SCHUKO)	3	
Residual current circuit breaker (RCCB)	no	
With cover lid	no	
Material	Plastic	
Impact strength	IK00	
Transparent	no	
With miniature fuse	no	
Number of socket outlets with earth pin	0	
Number of other socket outlets	0	
Number of cold device socket outlets	0	
Number of USB connections	0	
Number of socket outlets type Bipasso (Italy)	0	
Number of socket outlets Type P11 (Italy)	0	
Number of NEMA-outlets	0	
Number of universal multi standard sockets	0	
Number of socket outlets French standard (Type E)	0	
Compatible with Apple HomeKit	no	
Compatible with Google Assistant	no	
Compatible with Amazon Alexa	no	
Nominal current	16.00 A	
Colour	anthracite	
core cross section	1.5 mm²	
Halogen free	yes	
Surface protection	Untreated	
Length of power cord	1.4 m	
With on/off switch	yes	
Mains filter	no	
Rotated central insert	yes	
Over voltage protection	no	
RAL-number (similar)	7016	
Number of socket outlets CEE 7/16 (EURO)	6	

Technical data		233805009
IFTTT support available		no
Number of socket outlets Swiss standard type 13		0
Number of socket outlets Swiss standard type 15		0
Number of socket outlets Swiss standard type 23		0
Number of socket outlets Swiss standard type 25		0
Number of socket outlets Italian standard type P17		0
Degree of protection		IP20
Material quality		Duroplast
NEMA designation		None
Surface finishing		Matt
Angle rotated central insert		35°
Type of mains connection		Plug CEE 7/4 (type F)
Number of socket outlets Danish standard (earthing pin)		0
Number of socket outlets British Standard BS1363		0
Anti-bacterial treatment		no
Number of socket outlets Italian standard type P30		0
Overcurrent protection		nein
Max. connected load		3680 W
Directly pluggable (without power cord)		nein
Type of plug		angled
Number of socket outlets CEE 7/1 (no protective contact)		0