

| Art.No. | article name |
|-----------|---|
| 234105009 | DUOversal PLUS 6=12, with illuminated switch (2-pole), with shutter, with 35° turned sockets, cable 1.4m, mountable |

DUOversal Plus, 6=12, all sockets with connection option for one grounding-type plug or two euro-plugs, with illuminated switch (2-pole), with shutter, with 35° turned sockets, 52mm distance between sockets, cable H05VV-F3G1, 5mm², 1,4m, mountable, 16A, 250V~, anthracite



| Technical data | 234105009 |
|---|---------------------|
| Housing shape | Rectangular |
| Number of socket outlets with protective contact (SCHUKO) | 6 |
| Residual current circuit breaker (RCCB) | no |
| With cover lid | no |
| Material | Plastic |
| Impact strength | IK00 |
| Transparent | no |
| With miniature fuse | no |
| Number of socket outlets with earth pin | 0 |
| Number of other socket outlets | 0 |
| Number of cold device socket outlets | 0 |
| Number of USB connections | 0 |
| Number of socket outlets type Bipasso (Italy) | 0 |
| Number of socket outlets Type P11 (Italy) | 0 |
| Number of NEMA-outlets | 0 |
| Number of universal multi standard sockets | 0 |
| Number of socket outlets French standard (Type E) | 0 |
| Compatible with Apple HomeKit | no |
| Compatible with Google Assistant | no |
| Compatible with Amazon Alexa | no |
| Nominal current | 16.00 A |
| Colour | anthracite |
| core cross section | 1.5 mm ² |
| Halogen free | yes |
| Surface protection | Untreated |
| Length of power cord | 1.4 m |
| With on/off switch | yes |
| Mains filter | no |
| Rotated central insert | yes |
| Over voltage protection | no |
| RAL-number (similar) | 7016 |
| Number of socket outlets CEE 7/16 (EURO) | 12 |

| Technical data | | 234105009 |
|--|-----------------------|-----------|
| IFTTT support available | no | |
| Number of socket outlets Swiss standard type 13 | 0 | |
| Number of socket outlets Swiss standard type 15 | 0 | |
| Number of socket outlets Swiss standard type 23 | 0 | |
| Number of socket outlets Swiss standard type 25 | 0 | |
| Number of socket outlets Italian standard type P17 | 0 | |
| Degree of protection (IP) | IP20 | |
| Material quality | Duroplast | |
| NEMA designation | None | |
| Surface finishing | Matt | |
| Angle rotated central insert | 35° | |
| Type of mains connection | Plug CEE 7/4 (type F) | |
| Number of socket outlets Danish standard (earthing pin) | 0 | |
| Number of socket outlets British Standard BS1363 | 0 | |
| Anti-bacterial treatment | no | |
| Number of socket outlets Italian standard type P30 | 0 | |
| Overcurrent protection | nein | |
| Max. connected load | 3680 W | |
| Directly pluggable (without power cord) | nein | |
| Type of plug | angled | |
| Number of socket outlets CEE 7/1 (no protective contact) | 0 | |
| Packaging break | N | |