

Art.No.	article name
234505001	DUOversal PLUS 6=12, with overvoltage filter, illumination switch, with shutter, mountable, 35° turned sockets, 1.4m cable

DUOversal Plus, 6=12, with overvoltage filter, optical overvoltage indicator in case of a fault, all sockets with connection option for one grounding-type plug or two euro-plugs, with illuminated switch (2-pole), with shutter, with 35° turned sockets, 52mm distance between sockets, cable H05VV-F3G1, 5mm², 1,4m, mountable, 16A, 250V~, anthracite



Technical data	234505001
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	6
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Plastic
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	anthracite
core cross section	1.5 mm ²
Halogen free	yes
Surface protection	Untreated
Length of power cord	1.4 m
With on/off switch	yes
Mains filter	no
Rotated central insert	yes
Over voltage protection	yes
RAL-number (similar)	7016
Number of socket outlets CEE 7/16 (EURO)	12

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data		234505001
IFTTT support available		no
Number of socket outlets Swiss standard type 13		0
Number of socket outlets Swiss standard type 15		0
Number of socket outlets Swiss standard type 23		0
Number of socket outlets Swiss standard type 25		0
Number of socket outlets Italian standard type P17		0
Degree of protection (IP)		IP20
Material quality		Duroplast
NEMA designation		None
Surface finishing		Matt
Angle rotated central insert		35°
Type of mains connection		Plug CEE 7/4 (type F)
Number of socket outlets Danish standard (earthing pin)		0
Number of socket outlets British Standard BS1363		0
Anti-bacterial treatment		no
Number of socket outlets Italian standard type P30		0
Overcurrent protection		nein
Max. connected load		3680 W
Directly pluggable (without power cord)		nein
Type of plug		angled
Number of socket outlets CEE 7/1 (no protective contact)		0
Packaging break		N