

Art.No.	article name
297229081	ATHENIS - Flush-mounted socket outlet with earthing contact, USB A/C charging socket, colour: anthracite

ATHENIS - Flush-mounted socket outlet with earthing contact, USB A charging socket and USB C charging socket, output current charging sockets max. 3A, 5V, 55x55mm covers, rated current 16A, rated voltage 250V~, color: pure white



Technical data		297229081
Connection type	Push-in clamp	
With signal lamp	no	
With enhanced contact protection	yes	
Frequency	50 - 60	
Label space/information surface	no	
Eject-mechanism	no	
Material	Plastic	
Rated fault current	0.00 A	
Type of fastening	Mounting with claw and screw	
Impact strength	IK00	
Transparent	no	
With miniature fuse	no	
With loop through function	yes	
With function lighting	no	
With orientation lighting	no	
Number of modules (module system)	1	
Number of active pins (round)	0	
Number of active pins (flat)	2	
Min. depth of built-in installation box	31.5 mm	
Compatible with Apple HomeKit	no	
Compatible with Google Assistant	no	
Compatible with Amazon Alexa	no	
Metallic colour	no	
Nominal current	16.00 A	
Nominal voltage	250 V	
Mounting method	EV000383 - Flush-mounted (plaster)	
Colour	White	
Model	Socket outlet CEE 7/3 (type F)	
Halogen free	yes	
Lockable	no	
With hinged lid	no	
Surface protection	Untreated	
Number of phases	1	
With on/off switch	no	

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 15.09.2025

Technical data		297229081
For heavy conditions (according to VDE)	no	
Rotated central insert	no	
Over voltage protection	no	
Fault current protection	no	
Insulated mounting	no	
RAL-number (similar)	9010	
Width of device	55.0 mm	
Height of device	55.0 mm	
Depth of device	31.0 mm	
Number of socket outlets switchable	0	
IFTTT support available	no	
Concurrently switching neutral conductor	no	
Special power supply	No special power supply	
Material quality	Thermoplastic	
Surface finishing	Glossy	
Imprint/indication	None	
Suitable for degree of protection	IP20	
Anti-bacterial treatment	no	
With built-in bluetooth speaker	nein	
Number of ports USB-A	0	
Number of ports USB-C	0	
Max. current rating of USB power supply	3.00 A	
With Wi-Fi signal repeater	nein	
Colour of switch operator	farblos	
Protective contact	Earthing clips	
Device diameter	55.00 mm	
Concurrently switching neutral conductor	0	
Number of loop throughs	1	
Installation depth in mm	31.5 mm	