

Art.No.	article name
297247519	ATHENIS - flush-mounted socket outlet with earthing contact, USB A/C charging socket, colour: steel

ATHENIS - flush-mounted socket outlet with earthing contact, USB A charging socket and USB C charging socket, output current charging sockets max. 3A, 5V, 55x55mm covers, rated current 16A, rated voltage 250V~, in techniccenter-packaging, colour: steel



Technical data	297247519
Connection type	Push-in clamp
With signal lamp	no
With enhanced contact protection	yes
Frequency	50 - 60
Label space/information surface	no
Eject-mechanism	no
Material	Plastic
Rated fault current	0.00 A
Type of fastening	Mounting with claw and screw
Impact strength	IK00
Transparent	no
With miniature fuse	no
With loop through function	yes
With function lighting	no
With orientation lighting	no
Number of modules (module system)	1
Number of active pins (round)	0
Number of active pins (flat)	2
Min. depth of built-in installation box	31.5 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Metallic colour	no
Nominal current	16.00 A
Nominal voltage	250 V
Mounting method	EV000383 - Flush-mounted (plaster)
Colour	steel
Model	Socket outlet CEE 7/3 (type F)
Halogen free	yes
Lockable	no
With hinged lid	no
Surface protection	Lacquered
Number of phases	1
With on/off switch	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 03.03.2026

Technical data	297247519
For heavy conditions (according to VDE)	no
Rotated central insert	no
Over voltage protection	no
Fault current protection	no
Insulated mounting	no
Width of device	55.0 mm
Height of device	55.0 mm
Depth of device	31.0 mm
Number of socket outlets switchable	0
IFTTT support available	no
Concurrently switching neutral conductor	no
Material quality	Thermoplastic
Surface finishing	Matt
Imprint/indication	None
Suitable for degree of protection	IP20
Anti-bacterial treatment	no
With built-in bluetooth speaker	nein
Number of ports USB-A	0
Number of ports USB-C	0
Max. current rating of USB power supply	3.00 A
With Wi-Fi signal repeater	no
Colour of switch operator	farblos
Protective contact	Earthing clips
Device diameter	55.00 mm
Concurrently switching neutral conductor	0
Number of loop throughs	1