

Art.No.	article name
346701000	Cavity wall switch box with press-out membranes, Ø68mm, depth: 47mm, orange, IP30

Cavity wall switch box with press-out membranes, Ø68mm, depth: 47mm, orange, IP30, material: PP/TPE, windproof, easy to install due to tool-free cable and pipe insertion, with integrated cable retention for NYM cables, secure fixing of the pipes



Technical data	346701000
Shape	EV000167 - round
Diameter	68.0 mm
Internal depth	47.0 mm
Sealable	no
With screening	no
With nail lugs	no
With screws	yes
Inlet from the rear	yes
Pipe locking	no
Provided with revolving ring	no
Housing feed-through by seal membrane	yes
Housing feed-through by nozzle	no
Housing feed-through by step membrane	no
Pipe locking optional	no
Number of included spouts	0
Transparent cover	no
Colour	Orange
Model	Single
Halogen free	no
Surface protection	Untreated
Connectable	yes
Luminaire hook mounting	no
Max. conductor cross section	2.50 mm ²
Housing feed-through by break-out opening	yes
Air tight	yes
Degree of protection (IP)	IP30
Equipped with	None
Construction type	Built-in installation box (device box)
Circuit integrity	None
Cover model	None
Mounting switching equipment	Screw or spread out
For tube diameter	25 mm
Nozzle	None

Technical data		346701000
Depth	47,0 47,0 mm	
Number of inlets	6	
Suitable for wall/board thickness	40.000 mm	
Clamp position fixed	mo	