

Art.No.	article name
348601509	Cavity wall switch box with press-out membranes, Ø68mm, depth: 62mm, orange, IP30, profi-pack: 15 pcs.

Cavity wall switch box with press-out membranes, Ø68mm, depth: 62mm, orange, IP30, material: PP/TPE, windproof, easy to install due to tool-free cable and pipe insertion, with integrated cable retention for NYM cables, secure fixing of the pipes, incl. airtight connecting piece, profi-pack: 15 pcs.



Technical data		348601509
Shape		EV000167 - round
Diameter		68.0 mm
Internal depth		61.0 mm
Sealable		no
With screening		no
With nail lugs		no
With screws		yes
Inlet from the rear		yes
Pipe locking		no
Provided with revolving ring		no
Housing feed-through by seal membrane		yes
Housing feed-through by nozzle		no
Housing feed-through by step membrane		no
Pipe locking optional		no
Number of included spouts		0
Transparent cover		no
Colour		Orange
Model		Single
Halogen free		yes
Surface protection		Untreated
Luminaire hook mounting		no
Max. conductor cross section		2.50 mm ²
Air tight		yes
Equipped with		Other
Construction type		Built-in installation box (device box)
Circuit integrity		None
Cover model		None
Mounting switching equipment		Screw or spread out
For tube diameter		25 mm
Nozzle		None
Depth		62,0 62,0 mm
Number of inlets		8
Suitable for wall/board thickness		40.000 mm

Technical data		348601509
Clamp position fixed	mo	
Packaging break	N	