

Art.No.	article name
354302504	Switch box, flush-mounted, diameter: 60mm, depth: 65mm, profi-pack: 25 pcs., IP20, colour: black

Switch box, flush mounted, diameter: 60mm, depth: 65mm, with 13x M20 and 4x M25 conduit entries, 4x screw dome and 2x surface for expansion claw springs, max. surrounding temperature: -25°C to 40°C, profi-pack: 25 pcs., IP20, colour: black



Technical data		354302504
Shape	EV000167 - round	
Diameter	60.0 mm	
Internal depth	65.0 mm	
Length	6.0 mm	
Sealable	no	
Material	Polystyrene	
With screening	no	
With screws	no	
Inlet from the rear	yes	
Number of poles of the clamp	0	
Provided with revolving ring	no	
Housing feed-through by seal membrane	no	
Housing feed-through by nozzle	no	
Housing feed-through by step membrane	no	
Number of included spouts	0	
Transparent cover	no	
Colour	Black	
Model	Single	
Halogen free	yes	
Surface protection	Untreated	
Connectable	yes	
Luminaire hook mounting	no	
Air tight	no	
Degree of protection (IP)	IP20	
Construction type	Built-in installation box (device box)	
Mounting switching equipment	Screw or spread out	
For tube diameter	20/25 mm	
Special application	None	
Nozzle	None	
Depth	65.0 - 65.0	
Clamp position fixed	no	