Art.No.	article name
371800003	Wall outlet box with cover, diameter: 60mm, depth: 49mm, orange

Wall outlet box, diameter: 60mm, single gang, with 4 mounting lugs, interlinkable in 71 mm distance, installation heigt 49 mm, max. 2 conduit entries up to Ø25mm, orange

Technical data	*371800003*
Shape	EV000167 - round
Diameter	60.0 mm
Internal depth	49.0 mm
Length	49.0 mm
Sealable	no
Material	Polyethylene (PE)
With screening	no
With screws	No
Inlet from the rear	no
Pipe locking	no
Number of poles of the clamp	0
Provided with revolving ring	no
Housing feed-through by seal membrane	no
Housing feed-through by nozzle	no
Housing feed-through by step membrane	no
Pipe locking optional	no
Number of included spouts	0
Transparent cover	no
Mounting method	Concrete building
Colour	Orange
Width	60.0 mm
Model	Single
Halogen free	yes
Surface protection	Untreated
Connectable	yes
Luminaire hook mounting	no
Housing feed-through by break-out opening	yes
Air tight	no
Degree of protection (IP)	IP30
Equipped with	None
Construction type	Built-in installation box (device box)
Circuit integrity	None
Cover model	None
Mounting switching equipment	Screwing

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *10.08.2026*

Technical data	*371800003*
Cover attachment	Snapped on
For tube diameter	25 mm
Special application	None
Nozzle	None
Depth	49.0 - 49.0 mm
Suitable for cable diameter	25 - 25 mm
Number of inlets	2
For number of electric fittings	1
Clamp position fixed	mo
Number of non-adjustable device fixing lugs	0
Number of adjustable device fixing lugs	0
Mit Trennwand	no
Compliant with BS 4662	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *10.08.2026*