

Art.No.	article name
540256000	Off switch, 2-pole

Surface Mount, off-switch, 2-pole, printed pad "O-I", 10AX, 250V~, proAQA, light-grey/ dark-grey



Technical data	540256000
Connection type	Push-in clamp
Feedback-signal contact	no
Material	Plastic
Type of fastening	Screw mounting
Number of rockers	1
Impact strength	IK00
Number of modules (module system)	1
Min. depth of built-in installation box	0.0 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal voltage	250
Mounting method	EV000384 - Surface mounted (plaster)
Assembly arrangement	Basic element with complete housing
Method of operation	Rocker/button
Colour	Grey
Halogen free	yes
With mounting plate	no
Surface protection	Untreated
Built-in depth	0.0 mm
Rated current	10.00 A
RAL-number (similar)	7035
Switching current for fluorescent lamps	10 AX
Push button switch	no
Width of device	75.0 mm
Height of device	75.0 mm
Depth of device	58.0 mm
IFTTT support available	no
Washing machine switch	no
Illumination	No
Material quality	Thermoplastic
Type of lighting	Other
Label space/information surface	No
Function lighting	Other
Surface finishing	Glossy

Technical data		540256000
Wiring system	2-pole switch	
Suitable for degree of protection (IP)	IP44	
Anti-bacterial treatment	no	
Compliant with UK Building Regulations Part M	no	
Colour of switch operator	sonstige	
Heating switch	nein	