Art.No.	article name
699715089	ATHENIS IP44 - Control switch, colour: anthracite

ATHENIS - Heating master switch with spring plate and sealing ring, nominal current 10A, nominal voltage 250V~, protection class IP44, colour: anthracite

Technical data	*699715089*
Connection type	Push-in clamp
Feedback-signal contact	no
Material	Plastic
Type of fastening	Mounting with claw and screw
Number of rockers	1
Impact strength	IK00
Number of modules (module system)	1
Min. depth of built-in installation box	34.0 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal voltage	250 V
Mounting method	EV000383 - Flush-mounted (plaster)
Assembly arrangement	Basic element with central cover plate
Method of operation	Rocker/button
Colour	anthracite
Halogen free	yes
With mounting plate	yes
Surface protection	Lacquered
Built-in depth	32.0 mm
Rated current	16.00 A
RAL-number (similar)	7016
Switching current for fluorescent lamps	10 AX
Push button switch	yes
Width of device	55.0 mm
Height of device	55.0 mm
Depth of device	45.8 mm
IFTTT support available	no
Washing machine switch	no
Illumination	Yes
Material quality	Thermoplastic
Label space/information surface	No
Surface finishing	Matt
Wiring system	Two-way switch
Suitable for degree of protection	IP44

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *06.08.2026*

Technical data	*699715089*
Anti-bacterial treatment	no
Compliant with UK Building Regulations Part M	no
Colour of switch operator	Colourless
Heating switch	Yes

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *06.08.2026*