

Art.No.	article name
752523093	Residual Current Device (RCD), 2-pole, A-Type, 25A, 0,30A

Residual Current Device (RCD), 1+N, rated current 25A, rated residual operating current  $I_{\Delta n}$  0,30A, rated voltage 230 VAC, A-Type

Technical data	752523093
Voltage type	AC Hz
Rated insulation voltage $U_i$	440 V
Number of poles	2
Rated fault current	0.30 A
Surge current capacity	0.400 kA
Pollution degree	2
Connectable conductor cross section solid-core	1,00 25,00 mm <sup>2</sup>
Connectable conductor cross section multi-wired	1,00 25,00 mm <sup>2</sup>
With interlocking device	no
Additional equipment possible	yes
Mounting method	DIN rail
Built-in depth	68.0 mm
Rated current	25.00 A
Rated voltage	230 V
Width in number of modular spacings	2.0
Explosion-proof	no
Ambient temperature during operating	-25 55 °C
Rated impulse withstand voltage $U_{imp}$	4.00 kV
Degree of protection (IP)	IP20
Leakage current type	A
Frequency	50/60 Hz
Short-time delayed tripping	no
Short-circuit breaking capacity ( $I_{cw}$ )	10.000 kA
Selective protection	no

