

Art.No. article name

805800010 INFRAcontrol T 180°, infrared motion switch, 2-wire, 40 - 400 W

INFRAcontrol T 180° UP IP20, flush mounted infrared motion switch with slide switch: permanently OFF, automatic, permanently ON, 230V~, 50- 60Hz, 2-wire device for resistive loads 40-400W, twilight threshold infinitely variable, detection angle approx. 180°, complete device with frame, Protection type IP20, can be combined with the programs EUROPA/PARIS/MALTA, arctic-white



Technical data

805800010

Connection type	Screwed terminal
Height	57.0 mm
Depth	29.6 mm
Voltage type	AC Hz
Switching-on delay	4 s
Switch-off delay	240 s
Frequency	0 50 Hz
Staircase monitoring	no
Bridging switch	no
Suitable for wireless transmission	no
Max. switching power	400 W
Material	Plastic
Dim function with dimmer basic element	no
Diameter detection range on floor	10.00 m
Remote operation	no
Impact strength	IK00
Nominal voltage	230,00 230,00 V
With alarm function	no
Transparent	no
Detection angle horizontal	0 180 °
Min. switch-on time	4 s
Max. duty cycle	4 min
Optimum mounting height	1.1 m
With DALI interface	no
Min. depth of built-in installation box	32.0 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Max. switching power LED	0 W
Mounting method	Flush mounted
Colour	White
Width	57.0 mm

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 27.03.2024

Technical data		805800010
Model	Movement sensor	
Halogen free	yes	
Surface protection	Untreated	
Creep-under protection	no	
Built-in depth	31.8 mm	
With remote control	no	
Suitable for wall mounting	yes	
Max. transmission range frontally	10.000 m	
Max. transmission range sideways	10.000 m	
Temperature	0 50 °C	
Max. starting current	1.60 A	
HVAC-control	no	
Constant light control	no	
Substation input	no	
RAL-number (similar)	9003	
With signal unit	no	
Teach-function for response value luminosity	no	
Networkable	no	
Forced switch off	no	
Response value luminosity adjustable	yes	
IFTTT support available	no	
Degree of protection (IP)	IP20	
Animal zone	yes	
Material quality	Thermoplastic	
Surface finishing	Matt	
Response value sensitivity adjustable	ja	
Anti-bacterial treatment	no	
Suitable for ceiling mounting	nein	