

| Art.No.   | article name   |
|-----------|--|
| 805813010 | INFRAcontrol T 180° (EUROPA), IR-motion sensor, 2-wire, for ohmic load 40-400 W, incl. cover frame |

INFRAcontrol 2D 180° UP IP20, Flush mounted infrared motion switch, complete device with cover frame (Design EUROPA), detection angle: 180°, detection range: approx. 10m, switching time: 4-240 seconds, light threshold adjustable with slide switch: permanently OFF, automatic, permanently ON, 2-wire device for resistive loads 40-400W, 230V~, 50/60HZ, arctic-white



| Technical data                          | 805813010       |
|---|-----------------|
| Height                                  | 57.0 mm         |
| Depth                                   | 29.6 mm         |
| Voltage type                            | AC Hz           |
| Bridging switch                         | no              |
| Suitable for wireless transmission      | no              |
| Max. switching power                    | 400 W           |
| Dim function with dimmer basic element  | no              |
| Suitable for C-load                     | no              |
| Diameter detection range on floor       | 10.00 m         |
| Remote operation                        | no              |
| Impact strength                         | IK00            |
| Nominal voltage                         | 230,00 230,00 V |
| With alarm function                     | no              |
| Transparent                             | no              |
| Min. switch-on time                     | 4 s             |
| Max. duty cycle                         | 4 min           |
| Optimum mounting height                 | 1.1 m           |
| With DALI interface                     | no              |
| Min. depth of built-in installation box | 32.0 mm         |
| Compatible with Apple HomeKit           | no              |
| Compatible with Google Assistant        | no              |
| Compatible with Amazon Alexa            | no              |
| Colour                                  | White           |
| Width                                   | 57.0 mm         |
| Model                                   | Movement sensor |
| Halogen free                            | yes             |
| Surface protection                      | Untreated       |
| Creep-under protection                  | no              |
| Built-in depth                          | 31.8 mm         |
| With remote control                     | no              |
| Suitable for wall mounting              | yes             |
| Max. transmission range frontally       | 10.000 m        |
| Max. transmission range sideways        | 10.000 m        |

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 27.03.2024

| Technical data                               |      | 805813010 |
|--|------|-----------|
| HVAC-control                                 | no   |           |
| Constant light control                       | no   |           |
| With signal unit                             | no   |           |
| Teach-function for response value luminosity | no   |           |
| Networkable                                  | no   |           |
| Forced switch off                            | no   |           |
| Response value luminosity adjustable         | yes  |           |
| Animal zone                                  | no   |           |
| Surface finishing                            | Matt |           |
| Response value sensitivity adjustable        | nein |           |
| Anti-bacterial treatment                     | no   |           |