

Art.No.	article name
808102014	INFRAcontrol T 180°, complete, infrared motion switch, 2-wire, 40 - 400 W

INFRAcontrol 2D 180° UP IP20 Flush mounted infrared motion switch, complete device with cover frame (Design PARIS), detection angle: 180°, detection range: approx. 10m, switching time: 4-240 seconds, lightthreshold adjustable with slide switch: permanently OFF, automatic, permantly ON, 2-wire device for resistive loads 40-400W, 230V~, 50/60Hz, arctic-white



Technical data	808102014
Connection type	Screwed terminal
Height	57.0 mm
Depth	29.6 mm
Voltage type	AC Hz
Staircase monitoring	no
Bridging switch	no
Suitable for wireless transmission	no
Max. switching power	400 W
Dim function with dimmer basic element	no
Diameter detection range on floor	10.00 m
Remote operation	no
Impact strength	IK00
Nominal voltage	230,00 230,00 V
With alarm function	no
Transparent	no
Min. switch-on time	4 s
Max. duty cycle	4 min
Optimum mounting height	1.1 m
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Colour	White
Model	Movement sensor
Halogen free	yes
Surface protection	Untreated
Creep-under protection	no
Suitable for wall mounting	yes
Max. transmission range frontally	10.000 m
Max. transmission range sideways	10.000 m
Max. starting current	1.60 A
HVAC-control	no
Constant light control	no
Substation input	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 27.03.2024

Technical data		808102014
With signal unit	no	
Teach-function for response value luminosity	no	
Networkable	no	
Forced switch off	no	
Response value luminosity adjustable	yes	
Animal zone	no	
Surface finishing	Matt	
Response value sensitivity adjustable	nein	
Anti-bacterial treatment	no	