

Art.No.	article name
822101028	INFRAcontrol motion detector DeckUP 360°, flush mounting, 12m detection range, 1 channel

INFRAcontrol motion detector DeckUP 360° Infrared detection, 360° detection angle, flush mounting, detection range up to 12 m, protection class IP20, 230 VAC, 50 Hz, 1 channel to switch light, Incandescent lamps: 2,000 W High-voltage halogen lamps: 1,000 VA Fluorescent lamps: 500 VA Energy saving lamp: 360 VA LED: 360 W/VA; Lag time 5 sec. - 12 min, Response brightness 20 - 300 Lux; colour white, Remote control (IR remote control optional)



Technical data	822101028
Connection type	Screwed terminal
Height	83.0 mm
Voltage type	AC Hz
Switching-on delay	0 s
Switch-off delay	0 s
Frequency	50 50 Hz
Diameter	96.0 mm
Staircase monitoring	no
Bridging switch	no
Suitable for wireless transmission	no
Max. switching power	2000 W
Material	Plastic
Dim function with dimmer basic element	no
Response value luminosity	20 300 lx
Suitable for C-load	yes
Diameter detection range on floor	12.00 m
Remote operation	yes
Impact strength	IK01
Nominal voltage	230,00 230,00 V
With alarm function	no
Transparent	no
Detection angle horizontal	360 360 °
Min. switch-on time	5 s
Max. duty cycle	12 min
Optimum mounting height	2.5 m
Pivoting range sensor, horizontal	0 0 °
Pivoting range sensor, vertical	0 0 °
With DALI interface	no
Min. depth of built-in installation box	66.0 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data	822101028
Max. switching power LED	360 W
Mounting method	other
Colour	White
Model	Movement sensor
Halogen free	no
Surface protection	Untreated
Creep-under protection	no
Built-in depth	33.0 mm
With remote control	no
Built-in diameter	56.0 mm
Suitable for wall mounting	no
Max. transmission range frontally	3.000 m
Max. transmission range sideways	6.000 m
Temperature	0 40 °C
Max. starting current	8.00 A
HVAC-control	no
Constant light control	no
Substation input	no
RAL-number (similar)	9010
With signal unit	no
Control current	0.00 mA
Teach-function for response value luminosity	no
Networkable	no
Forced switch off	no
Response value luminosity adjustable	yes
IFTTT support available	no
Forced switch on	no
Max. presence range	.000 m ²
Degree of protection (IP)	IP20
Animal zone	no
Material quality	Thermoplastic
Surface finishing	Matt
Sensor type	Passive infrared
Response value sensitivity adjustable	ja
Anti-bacterial treatment	no
Suitable for ceiling mounting	ja
Packaging break	J