

Art.No. article name

823805017 INFRAcontrol R 180°, IR-motion sensor, 3-wire, ohmic/inductive load 1000W

INFRAcontrol R 180° AP IP44, Flush mounted infrared motion switch, detection angle:180° universally adjustable, detection range: approx.12m, switching time: 5-720 seconds, light treshold adjustable 3-wire device for resistive and inductive loads 1000W, 230V~,50/60Hz, black



Technical data 823805017

Connection type	Screwed terminal
Voltage type	AC Hz
Switch-off delay	0 s
Staircase monitoring	no
Bridging switch	no
Suitable for wireless transmission	no
Max. switching power	1500 W
Material	Plastic
Dim function with dimmer basic element	no
Response value luminosity	20 300 lx
Suitable for C-load	yes
Diameter detection range on floor	24 m
Remote operation	no
Impact strength	IK00
Nominal voltage	230 230 V
With alarm function	no
Transparent	no
Detection angle horizontal	0 180 °
Min. switch-on time	5 s
Max. duty cycle	12 min
Optimum mounting height	2.5 m
Pivoting range sensor, horizontal	-35 35 °
Pivoting range sensor, vertical	-15 15 °
With DALI interface	no
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Max. switching power LED	300 W
Mounting method	Surface mounted
Colour	Black
Model	Movement sensor
Halogen free	yes
Surface protection	Untreated
Creep-under protection	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 23.04.2024

Technical data		823805017
With remote control	no	
Max. transmission range frontally	5.000 m	
Max. transmission range sideways	12.000 m	
Temperature	-10 50 °C	
Max. starting current	16.00 A	
HVAC-control	no	
Constant light control	no	
Substation input	no	
RAL-number (similar)	9005	
With signal unit	no	
Control current	0.00 mA	
Teach-function for response value luminosity	no	
Networkable	no	
Forced switch off	no	
Response value luminosity adjustable	yes	
IFTTT support available	no	
Forced switch on	no	
Max. presence range	0 m <sup>2</sup>	
Degree of protection (IP)	IP44	
Animal zone	no	
Material quality	Thermoplastic	
Surface finishing	Matt	
Sensor type	Passive infrared	
Response value sensitivity adjustable	nein	
Anti-bacterial treatment	no	
Suitable for ceiling mounting	nein	