

Art.No.	article name
827804003	Presence detector PM360-DE-12-S-ws, ceiling installation, 12m detection range, Slave

Presence detector PM360-DE-12-S-ws, 360° detection angle, ceiling mounting, detection range up to 12 m, Protection class IP20, Infrared detection, Slave, white, 230 VAC, 50 Hz



Technical data	827804003
Connection type	Push-in clamp
Depth	75.5 mm
Voltage type	AC Hz
Frequency	50 50 Hz
Diameter	111.5 mm
Staircase monitoring	no
Bridging switch	no
Suitable for wireless transmission	no
Max. switching power	0 W
Material	Plastic
Dim function with dimmer basic element	no
Suitable for C-load	no
Diameter detection range on floor	12.00 m
Remote operation	no
Impact strength	IK02
Nominal voltage	230,00 230,00 V
With alarm function	no
Transparent	no
Detection angle horizontal	360 360 °
Min. switch-on time	0 s
Max. duty cycle	0 min
Optimum mounting height	2.5 m
Pivoting range sensor, horizontal	0 0 °
Pivoting range sensor, vertical	0 0 °
With DALI interface	no
Min. depth of built-in installation box	47.0 mm
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Max. switching power LED	0 W
Mounting method	other
Colour	White
Model	Presence detector
Halogen free	yes
Surface protection	Lacquered

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 20.03.2024

Technical data	827804003
Creep-under protection	no
Built-in depth	41.0 mm
With remote control	no
Built-in diameter	65.0 mm
Suitable for wall mounting	no
Max. transmission range frontally	2.500 m
Max. transmission range sideways	6.000 m
Temperature	-20 50 °C
Max. starting current	0.00 A
HVAC-control	no
Constant light control	no
Substation input	no
RAL-number (similar)	9010
With signal unit	no
Teach-function for response value luminosity	no
Networkable	no
Forced switch off	yes
Response value luminosity adjustable	no
IFTTT support available	no
Forced switch on	yes
Min. starting current	0.00 A
Max. presence range	12.500 m <sup>2</sup>
Degree of protection (IP)	IP20
Animal zone	no
Material quality	Thermoplastic
Surface finishing	Matt
Sensor type	Passive infrared
Response value sensitivity adjustable	nein
Anti-bacterial treatment	no
Suitable for ceiling mounting	ja
Packaging break	J