


Art.No.	article name
845000007	Universal dimmer LED 3-170W

Universal dimmer-socket, for all flush-mounted switch range (RLC), recognize if phase alignment or phase control, LED 3-100W/VA, max. 200W/VA, with shaft adapter 4 to 6mm



Technical data	845000007
Connection type	Screwed terminal
Frequency	50 60 Hz
Material	Metal
Type of fastening	Mounting with claw and screw
Impact strength	IK00
Nominal voltage	230,00 230,00 V
Control voltage	230 230 V
Transparent	no
Number of modules (module system)	1
Dimming phase cut-off	yes
Dimming phase cut-on	yes
Min. depth of built-in installation box	32.0 mm
Nominal power resistive load	3 300 W
Nominal power inductive load	3 300 VA
Nominal power capacitive load	3 300 VA
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Max. switching power LED	170 W
Mounting method	Flush mounted
Assembly arrangement	Basic element
Method of operation	Turn/push button
Colour	aluminium
Halogen free	yes
Surface protection	Untreated
Light value memory	yes
Substation input	yes
RAL-number (similar)	9006
Serial dimmer	no
Applicable with movement sensor	no
Applicable with transmission button	no
Applicable with infrared button	no
Applicable with presence indicator	no
Applicable with button	yes
Applicable with time switch/timer	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 27.03.2024

Technical data		84500007
Width of device	71.0 mm	
Height of device	71.0 mm	
Depth of device	47.0 mm	
Core cross section	1,5 2,5 mm <sup>2</sup>	
IFTTT support available	no	
App control via Bluetooth	no	
Material quality	Stainless steel	
Type of load	Universal	
Surface finishing	Glossy	
Suitable for degree of protection (IP)	IP20	
Min. brightness controllable	ja	