

| Art.No.   | article name                                 |
|-----------|----------------------------------------------|
| 845000186 | Push-changeover universal dimmer, LED 3-170W |

Changeover switch - LED dimmer - for incandescent and 230V halogen lamps, LED 3-170W, also suitable for changeover switching with switch or push-button, max. 300W/VA



| Technical data                          |                              | 845000186 |
|-----------------------------------------|------------------------------|-----------|
| Frequency                               | 50 - 50                      |           |
| Material                                | Steel                        |           |
| Type of fastening                       | Mounting with claw and screw |           |
| Impact strength                         | IK00                         |           |
| Nominal voltage                         | 230 - 230                    |           |
| Control voltage                         | 230 - 230                    |           |
| Transparent                             | no                           |           |
| Number of modules (module system)       | 1                            |           |
| Dimming phase cut-off                   | yes                          |           |
| Dimming phase cut-on                    | yes                          |           |
| Min. depth of built-in installation box | 32.0 mm                      |           |
| Nominal power resistive load            | 0 - 300                      |           |
| Nominal power inductive load            | 0 - 300                      |           |
| Nominal power capacitive load           | 0 - 300                      |           |
| Compatible with Apple HomeKit           | no                           |           |
| Compatible with Google Assistant        | no                           |           |
| Compatible with Amazon Alexa            | no                           |           |
| Max. switching power LED                | 170 W                        |           |
| Mounting method                         | Flush mounted                |           |
| Assembly arrangement                    | Basic element                |           |
| Method of operation                     | Turn/push button             |           |
| Colour                                  | aluminium                    |           |
| Halogen free                            | yes                          |           |
| Surface protection                      | Untreated                    |           |
| Light value memory                      | yes                          |           |
| Substation input                        | yes                          |           |
| Serial dimmer                           | no                           |           |
| Applicable with movement sensor         | no                           |           |
| Applicable with transmission button     | no                           |           |
| Applicable with infrared button         | no                           |           |
| Applicable with presence indicator      | no                           |           |
| Applicable with button                  | yes                          |           |
| Applicable with time switch/timer       | no                           |           |

| Technical data                    |             | 845000186 |
|-----------------------------------|-------------|-----------|
| Width of device                   | 71.0 mm     |           |
| Height of device                  | 71.0 mm     |           |
| Depth of device                   | 47.0 mm     |           |
| Core cross section                | 1.5 - 2.5   |           |
| IFTTT support available           | no          |           |
| Material quality                  | Sheet steel |           |
| Type of load                      | Universal   |           |
| Surface finishing                 | Untreated   |           |
| Suitable for degree of protection | IP20        |           |
| Min. brightness controllable      | ja          |           |