

Art.No.	article name
845500181	Push-changeover universal dimmer, colour: aluminium

Push-changovering universal dimmer for incandescent lamps and 230V halogen lamps, dimmable LEDs and for LV/HV halogen lamps with transformers. Adjustable basic brightness, dimmable with leading edge and phase section possible, 5-250W/VA, LED 5-100W, shaft 4mm, with nut and shaft adapter, colour: aluminium



Technical data	845500181
Frequency	50 50 Hz
Material	Metal
Type of fastening	Mounting with claw and screw
Impact strength	IK00
Nominal voltage	230,00 230,00 V
Transparent	no
Number of modules (module system)	1
Dimming phase cut-off	yes
Dimming phase cut-on	yes
Min. depth of built-in installation box	34.0 mm
Nominal power resistive load	5 250 W
Nominal power inductive load	5 250 VA
Nominal power capacitive load	5 250 VA
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Max. switching power LED	100 W
Mounting method	EV000383 - Flush-mounted (plaster)
Assembly arrangement	Basic element
Method of operation	Turn/push button
Colour	aluminium
Halogen free	yes
Surface protection	Untreated
Light value memory	yes
Substation input	yes
RAL-number (similar)	9006
Serial dimmer	no
Applicable with movement sensor	no
Applicable with transmission button	no
Applicable with infrared button	no
Applicable with presence indicator	no
Applicable with button	no
Applicable with time switch/timer	no

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 10.04.2024

Technical data		845500181
Width of device	71.0 mm	
Height of device	71.0 mm	
Depth of device	55.0 mm	
Core cross section	1,5 2,5 mm ²	
IFTTT support available	no	
Material quality	Aluminium	
Type of load	Universal	
Surface finishing	Glossy	
Suitable for degree of protection (IP)	IP20	