

| Art.No. | article name |
|---------|--------------|
|---------|--------------|

| | |
|-----------|---|
| 845832080 | ATHENIS - push-changeover universal-dimmer, colour: arctic white matt |
|-----------|---|

ATHENIS - push-changeover universal dimmer for incandescent lamps and 230V halogen lamps, dimmable LEDs and for LV halogen lamps with electronic transformers. Adjustable basic brightness, dimmable with leading edge and phase section possible, RC10-250W / VA, LED 5-100W, shaft 4mm, with nut and shaft adapter, colour: arctic white matt



| Technical data | 845832080 |
|---|--|
| Frequency | 50 50 Hz |
| Material | Metal |
| Type of fastening | Mounting with claw and screw |
| Impact strength | IK00 |
| Nominal voltage | 230 230 V |
| Transparent | no |
| Number of modules (module system) | 1 |
| Dimming phase cut-off | yes |
| Dimming phase cut-on | yes |
| Min. depth of built-in installation box | 33.0 mm |
| Nominal power resistive load | 10 250 W |
| Nominal power inductive load | 10 250 VA |
| Nominal power capacitive load | 10 250 VA |
| Compatible with Apple HomeKit | no |
| Compatible with Google Assistant | no |
| Compatible with Amazon Alexa | no |
| Max. switching power LED | 100 W |
| Assembly arrangement | Basic element with central cover plate |
| Method of operation | Turn/push button |
| Colour | White |
| Halogen free | yes |
| Surface protection | Lacquered |
| Light value memory | yes |
| Substation input | yes |
| RAL-number (similar) | 9016 |
| Serial dimmer | no |
| Applicable with movement sensor | no |
| Applicable with transmission button | no |
| Applicable with infrared button | no |
| Applicable with presence indicator | no |
| Applicable with button | yes |
| Applicable with time switch/timer | no |
| Width of device | 55.0 mm |

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 10.04.2024

| Technical data | | 845832080 |
|--|-------------------------|-----------|
| Height of device | 55.0 mm | |
| Depth of device | 33.0 mm | |
| Core cross section | 1,5 2,5 mm ² | |
| IFTT support available | no | |
| Material quality | Aluminium | |
| Type of load | Universal | |
| Surface finishing | Glossy | |
| Suitable for degree of protection (IP) | IP20 | |
| Min. brightness controllable | ja | |
| Farbe (Kopp-Bezeichnung) | arctic white | |