

| Art.No. | article name |
|---------|--------------|
|---------|--------------|

| | |
|-----------|--|
| 920602002 | HK05 - Earthed socket outlet with shutter - colour: arctic white |
|-----------|--|

HK05 - Earthed socket outlet with shutter - colour: arctic white

| Technical data | 920602002 |
|---|------------------------------------|
| Connection type | Push-in clamp |
| With signal lamp | no |
| With enhanced contact protection | yes |
| Frequency | 50 50 Hz |
| Label space/information surface | no |
| Eject-mechanism | no |
| Material | Plastic |
| Rated fault current | 250.00 A |
| Type of fastening | Mounting with claw and screw |
| Impact strength | IK00 |
| Transparent | no |
| With miniature fuse | no |
| With loop through function | yes |
| With function lighting | no |
| With orientation lighting | no |
| Number of modules (module system) | 1 |
| Number of active pins (round) | 2 |
| Number of active pins (flat) | 0 |
| Min. depth of built-in installation box | 32.0 mm |
| Compatible with Apple HomeKit | no |
| Compatible with Google Assistant | no |
| Compatible with Amazon Alexa | no |
| Metallic colour | no |
| Nominal current | 16.00 A |
| Nominal voltage | 250 |
| Mounting method | EV000383 - Flush-mounted (plaster) |
| Colour | White |
| Model | Socket outlet CEE 7/3 (type F) |
| Halogen free | yes |
| Lockable | no |
| With hinged lid | no |
| Surface protection | Untreated |
| Number of socket outlets | 1 |
| Number of phases | 1 |
| With on/off switch | no |
| For heavy conditions (according to VDE) | no |



| Technical data | | 920602002 |
|--|-------------------------|-----------|
| Rotated central insert | no | |
| Over voltage protection | no | |
| Fault current protection | no | |
| Insulated mounting | no | |
| RAL-number (similar) | 9016 | |
| Width of device | 57.0 mm | |
| Height of device | 57.0 mm | |
| Depth of device | 41.1 mm | |
| Number of socket outlets switchable | 0 | |
| IFTTT support available | no | |
| Concurrently switching neutral conductor | no | |
| Special power supply | No special power supply | |
| Material quality | Thermoplastic | |
| Surface finishing | Glossy | |
| Imprint/indication | None | |
| Suitable for degree of protection (IP) | IP20 | |
| Anti-bacterial treatment | no | |
| With built-in bluetooth speaker | nein | |
| Number of ports USB-A | 0 | |
| Number of ports USB-C | 0 | |
| Max. current rating of USB power supply | 0.00 A | |
| With Wi-Fi signal repeater | nein | |
| Colour of switch operator | farblos | |
| Protective contact | Earthing clips | |
| Concurrently switching neutral conductor | 0 | |
| Number of loop throughs | 0 | |
| Farbe (Kopp-Bezeichnung) | arctic white | |