

Art.No.	article name
930105013	PROFIversal PA 6-way, earthing system, with 3 separate power circuits, 19", 2m cable with CEE-plug

PROFIversal PA, 6-way, with 3 separate current circuits, with 45° turned sockets, 44,45mm distance between sockets, universally mountable, reconnectable, cable H05VV-F5G1,5mm², 2m, with CEE-plug 5-pole 16A, 16A, 250V~, length 482,6mm, VDE, CEE7/III, black



Technical data	930105013
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	6
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Metal
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Black
core cross section	1.5 mm ²
Halogen free	no
Surface protection	Untreated
Length of power cord	2 m
With on/off switch	no
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9005
Number of socket outlets CEE 7/16 (EURO)	0

Technical data		930105013
IFTTT support available		no
Number of socket outlets Swiss standard type 13		0
Number of socket outlets Swiss standard type 15		0
Number of socket outlets Swiss standard type 23		0
Number of socket outlets Swiss standard type 25		0
Number of socket outlets Italian standard type P17		0
Degree of protection (IP)		IP20
Material quality		Aluminium
NEMA designation		None
Surface finishing		Matt
Angle rotated central insert		45°
Number of socket outlets Danish standard (earthing pin)		0
Number of socket outlets British Standard BS1363		0
Anti-bacterial treatment		no
Number of socket outlets Italian standard type P30		0
Overcurrent protection		nein
Max. connected load		3680 W
Type of plug		angled
Number of socket outlets CEE 7/1 (no protective contact)		0