

| Art.No. | article name |
|-----------|--|
| 930904016 | PROFiversal 5-way, earthing system, with overvoltage filter, 2m cable, length: 671,4mm |

PROFiversal 9-way, with overvoltage filter SAFETRONIC and mains filter, optical and acoustic overvoltage indicator in case of a fault, with 45° turned sockets, 44,45mm distance between sockets, universally moutable, reconnectable, cable H05VV-F3G1,5mm², 2m, 16A, 250V~, length 671,4mm, VDE, CEE7/III, aluminium



| Technical data | 930904016 |
|---|---------------------|
| Housing shape | Rectangular |
| Number of socket outlets with protective contact (SCHUKO) | 9 |
| Residual current circuit breaker (RCCB) | no |
| With cover lid | no |
| Material | Metal |
| Impact strength | IK00 |
| Transparent | no |
| With miniature fuse | no |
| Number of socket outlets with earth pin | 0 |
| Number of other socket outlets | 0 |
| Number of cold device socket outlets | 0 |
| Number of USB connections | 0 |
| Number of socket outlets type Bipasso (Italy) | 0 |
| Number of socket outlets Type P11 (Italy) | 0 |
| Number of NEMA-outlets | 0 |
| Number of universal multi standard sockets | 0 |
| Number of socket outlets French standard (Type E) | 0 |
| Compatible with Apple HomeKit | no |
| Compatible with Google Assistant | no |
| Compatible with Amazon Alexa | no |
| Nominal current | 16.00 A |
| Colour | Grey |
| core cross section | 1.5 mm ² |
| Halogen free | no |
| Surface protection | Untreated |
| Length of power cord | 2 m |
| With on/off switch | no |
| Mains filter | yes |
| Rotated central insert | yes |
| Over voltage protection | yes |
| RAL-number (similar) | 9006 |
| Number of socket outlets CEE 7/16 (EURO) | 0 |

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 28.03.2024

| Technical data | | 930904016 |
|--|-----------|-----------|
| IFTTT support available | no | |
| Number of socket outlets Swiss standard type 13 | 0 | |
| Number of socket outlets Swiss standard type 15 | 0 | |
| Number of socket outlets Swiss standard type 23 | 0 | |
| Number of socket outlets Swiss standard type 25 | 0 | |
| Number of socket outlets Italian standard type P17 | 0 | |
| Degree of protection (IP) | IP20 | |
| Material quality | Aluminium | |
| NEMA designation | None | |
| Surface finishing | Matt | |
| Angle rotated central insert | 45° | |
| Number of socket outlets Danish standard (earthing pin) | 0 | |
| Number of socket outlets British Standard BS1363 | 0 | |
| Anti-bacterial treatment | no | |
| Number of socket outlets Italian standard type P30 | 0 | |
| Overcurrent protection | nein | |
| Max. connected load | 3680 W | |
| Type of plug | angled | |
| Number of socket outlets CEE 7/1 (no protective contact) | 0 | |