

Art.No.	article name
931305010	PROFIversal PA 6+6-way, earthing system, with illuminated switch 2-pole sockets on front and back, 19", 2m cable

PROFIversal PA, 6+6-way, with illuminated 2-pole switch, 6 sockets in front and backside, with 45° turned sockets, 44,45mm distance between sockets, universally mountable, reconnectable, cable H05VV-F3G1,5mm², 2m, 16A, 250V~, length 482,6mm, VDE, CEE7/III, black



Technical data	931305010
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	12
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Metal
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	16.00 A
Colour	Black
core cross section	1.5 mm ²
Halogen free	no
Surface protection	Untreated
Length of power cord	2 m
With on/off switch	yes
Mains filter	yes
Rotated central insert	yes
Over voltage protection	yes
RAL-number (similar)	9005
Number of socket outlets CEE 7/16 (EURO)	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 28.03.2024

Technical data		931305010
IFTTT support available		no
Number of socket outlets Swiss standard type 13		0
Number of socket outlets Swiss standard type 15		0
Number of socket outlets Swiss standard type 23		0
Number of socket outlets Swiss standard type 25		0
Number of socket outlets Italian standard type P17		0
Degree of protection (IP)		IP20
Material quality		Aluminium
NEMA designation		None
Surface finishing		Matt
Angle rotated central insert		45°
Number of socket outlets Danish standard (earthing pin)		0
Number of socket outlets British Standard BS1363		0
Anti-bacterial treatment		no
Number of socket outlets Italian standard type P30		0
Overcurrent protection		nein
Max. connected load		3680 W
Type of plug		angled