Art.No.	article name
931704011	PROFIversal 7-way, USV multiple socket, fuse 10A, 19", 2m cable

PROFIversal 7-way, for USV applications with integrated fuse 10A, with 45° turned sockets, 44,45mm distance between sockets, universally mountable, reconnectable, cable H05VV-F3G1,5mm², 2m, 10A, 250V~, length 482,6mm, VDE, CEE7/III, aluminium-red

Technical data	*931704011*
Housing shape	Rectangular
Number of socket outlets with protective contact (SCHUKO)	7
Residual current circuit breaker (RCCB)	no
With cover lid	no
Material	Metal
Impact strength	IK00
Transparent	no
With miniature fuse	no
Number of socket outlets with earth pin	0
Number of other socket outlets	0
Number of cold device socket outlets	0
Number of USB connections	0
Number of socket outlets type Bipasso (Italy)	0
Number of socket outlets Type P11 (Italy)	0
Number of NEMA-outlets	0
Number of universal multi standard sockets	0
Number of socket outlets French standard (Type E)	0
Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Nominal current	10.00 A
Colour	Grey
core cross section	1.5 mm²
UV resistant	conditionally
Halogen free	no
Surface protection	Untreated
Length of power cord	2 m
With on/off switch	no
Mains filter	no
Rotated central insert	yes
Over voltage protection	no
RAL-number (similar)	9006

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *07.08.2026*

Technical data	*931704011*
Number of socket outlets CEE 7/16 (EURO)	0
IFTTT support available	no
Number of socket outlets Swiss standard type 13	0
Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0
Number of socket outlets Italian standard type P17	0
Degree of protection (IP)	IP20
Material quality	Aluminium
NEMA designation	None
Surface finishing	Matt
Angle rotated central insert	45°
Type of mains connection	Plug CEE 7/4 (type F)
Number of socket outlets Danish standard (earthing pin)	0
Number of socket outlets British Standard BS1363	0
Anti-bacterial treatment	no
Number of socket outlets Italian standard type P30	0
Overcurrent protection	no
Max. connected load	3680 W
Directly pluggable (without power cord)	no
Type of plug	angled
Number of socket outlets CEE 7/1 (no protective contact)	0

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionverbesserungen bleiben ausdrücklich vorbehalten. Stand: *07.08.2026*