

Art.No.	article name
947506003	proAQA – Double earthed socket outlet with hinged lid, pre wired, colour: black

Surface Mount, Earthed socket with hinged lid, 2-fold, vertical, without shutter, prewired, 16A, 250V~, proAQA, black



Technical data		947506003
Connection type	Screw and Push-in clamp	
With signal lamp	no	
With enhanced contact protection	no	
Frequency	50 50 Hz	
Label space/information surface	no	
Eject-mechanism	no	
Material	Plastic	
Rated fault current	0.00 A	
Type of fastening	Mounting with screw	
Impact strength	IK00	
Transparent	no	
With miniature fuse	no	
With loop through function	yes	
With function lighting	no	
With orientation lighting	no	
Number of modules (module system)	2	
Number of active pins (round)	0	
Number of active pins (flat)	2	
Min. depth of built-in installation box	0.0 mm	
Compatible with Apple HomeKit	no	
Compatible with Google Assistant	no	
Compatible with Amazon Alexa	no	
Metallic colour	no	
Nominal current	16.00 A	
Nominal voltage	250 V	
Mounting method	Aufputz	
Colour	Black	
Model	Socket outlet CEE 7/3 (type F)	
Halogen free	yes	
Lockable	no	
With hinged lid	yes	
Surface protection	Untreated	
Number of phases	1	
With on/off switch	no	
For heavy conditions (according to VDE)	no	

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 18.04.2024

Technical data		947506003
Rotated central insert	no	
Over voltage protection	no	
Fault current protection	no	
Insulated mounting	no	
RAL-number (similar)	9005	
Width of device	75.0 mm	
Height of device	134.0 mm	
Depth of device	58.0 mm	
Number of socket outlets switchable	0	
IFTTT support available	no	
Concurrently switching neutral conductor	no	
Special power supply	No special power supply	
Material quality	Thermoplastic	
Surface finishing	Glossy	
Imprint/indication	None	
Suitable for degree of protection (IP)	IP44	
Anti-bacterial treatment	no	
With built-in bluetooth speaker	nein	
Number of ports USB-A	0	
Number of ports USB-C	0	
Max. current rating of USB power supply	0.00 A	
With Wi-Fi signal repeater	nein	
Colour of switch operator	sonstige	
Protective contact	flat	
Concurrently switching neutral conductor	0	
Number of loop throughs	1	