

Art.No.	article name
954756008	proAQA - Surface-mounted socket outlet with center earthing contact, color: grey

proAQA - Surface-mounted center socket outlet with increased touch protection, with hinged cover, rated current 16A and rated voltage 250V, protection class IP 44, color: grey



Technical data		954756008
Connection type	Push-in clamp	
With signal lamp	no	
With enhanced contact protection	yes	
Frequency	50 - 50	
Label space/information surface	no	
Eject-mechanism	no	
Material	Plastic	
Rated fault current	0.00 A	
Type of fastening	Mounting with screw	
Impact strength	IK00	
Transparent	no	
With miniature fuse	no	
With loop through function	yes	
With function lighting	no	
With orientation lighting	no	
Number of modules (module system)	1	
Number of active pins (round)	0	
Number of active pins (flat)	2	
Min. depth of built-in installation box	0.0 mm	
Compatible with Apple HomeKit	no	
Compatible with Google Assistant	no	
Compatible with Amazon Alexa	no	
Metallic colour	no	
Nominal current	16.00 A	
Nominal voltage	250 V	
Mounting method	Aufputz	
Colour	Grey	
Model	Grounding pin	
Halogen free	no	
Lockable	no	
With hinged lid	yes	
Surface protection	Untreated	
Number of phases	1	
With on/off switch	no	
For heavy conditions (according to VDE)	no	

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 18.08.2025

Technical data		954756008
Rotated central insert	no	
Over voltage protection	no	
Fault current protection	no	
Insulated mounting	no	
Width of device	75.0 mm	
Height of device	75.0 mm	
Depth of device	58.0 mm	
Number of socket outlets switchable	0	
IFTTT support available	no	
Concurrently switching neutral conductor	no	
Special power supply	No special power supply	
Material quality	Thermoplastic	
Surface finishing	Glossy	
Imprint/indication	None	
Suitable for degree of protection	IP44	
Anti-bacterial treatment	no	
With built-in bluetooth speaker	nein	
Number of ports USB-A	0	
Number of ports USB-C	0	
With Wi-Fi signal repeater	nein	
Colour of switch operator	sonstige	
Protective contact	round	
Concurrently switching neutral conductor	0	
Number of loop throughs	1	