

Art.No. article name

990015909 test package BLUE ELECTRIC®, colour: grey

test package BLUE ELECTRIC®, colour: grey



| Technical data 990015909                |                                |
|-----------------------------------------|--------------------------------|
| Connection type                         | Push-in clamp                  |
| With signal lamp                        | no                             |
| With enhanced contact protection        | no                             |
| Frequency                               | 50 - 50                        |
| Label space/information surface         | no                             |
| Eject-mechanism                         | no                             |
| Material                                | Plastic                        |
| Rated fault current                     | 0.00 A                         |
| Type of fastening                       | Mounting with screw            |
| Impact strength                         | not applicable                 |
| Transparent                             | no                             |
| With miniature fuse                     | no                             |
| With loop through function              | yes                            |
| With function lighting                  | no                             |
| With orientation lighting               | no                             |
| Number of modules (module system)       | 1                              |
| Number of active pins (round)           | 0                              |
| Number of active pins (flat)            | 2                              |
| Compatible with Apple HomeKit           | no                             |
| Compatible with Google Assistant        | no                             |
| Compatible with Amazon Alexa            | no                             |
| Metallic colour                         | no                             |
| Nominal current                         | 16.00 A                        |
| Nominal voltage                         | 250 V                          |
| Mounting method                         | Surface mounted                |
| Colour                                  | Grey                           |
| Model                                   | Socket outlet CEE 7/3 (type F) |
| Halogen free                            | yes                            |
| Lockable                                | no                             |
| With hinged lid                         | yes                            |
| Surface protection                      | Untreated                      |
| Number of phases                        | 1                              |
| With on/off switch                      | no                             |
| For heavy conditions (according to VDE) | yes                            |
| Rotated central insert                  | no                             |
| Over voltage protection                 | no                             |

Technische Beschreibungen, Abbildungen und Leistungsangaben stellen keine zugesagten Eigenschaften dar, sondern sind nur unverbindliche Informationen. Änderungen aufgrund technischen Fortschritts, Normänderungen, veränderter Fertigungsverfahren oder Konstruktionsverbesserungen bleiben ausdrücklich vorbehalten. Stand: 27.06.2025

| Technical data                           |                         | 990015909 |
|------------------------------------------|-------------------------|-----------|
| Fault current protection                 | no                      |           |
| Insulated mounting                       | no                      |           |
| RAL-number (similar)                     | 7035                    |           |
| Width of device                          | 78.0 mm                 |           |
| Height of device                         | 78.0 mm                 |           |
| Depth of device                          | 60.0 mm                 |           |
| Number of socket outlets switchable      | 0                       |           |
| IFTTT support available                  | no                      |           |
| Special power supply                     | No special power supply |           |
| Material quality                         | Thermoplastic           |           |
| Surface finishing                        | Glossy                  |           |
| Imprint/indication                       | Other                   |           |
| Suitable for degree of protection        | IP44                    |           |
| Anti-bacterial treatment                 | no                      |           |
| With built-in bluetooth speaker          | nein                    |           |
| Number of ports USB-A                    | 0                       |           |
| Number of ports USB-C                    | 0                       |           |
| With Wi-Fi signal repeater               | nein                    |           |
| Colour of switch operator                | grau                    |           |
| Protective contact                       | Earthing clips          |           |
| Concurrently switching neutral conductor | 0                       |           |
| Number of loop throughs                  | 1                       |           |